



MPO12 APC SMF Breakout Cables Datasheet

Applicable to Infiniband and Ethernet network architecture cabling



Standards Compliance

- YD/T1272.5-2019
- IEC 61300-3-35
- RoHS and REACH

Features

- G657.A1 Fiber
- Low loss ferrule
- Grinding method: APC
- Factory Pre-terminated 100% Tested
- Support InfiniBand, Ethernet network

Technical Specification


ITEM	Description
Fibre Count	8 Fibers
Fiber Mode	Single mode: G657.A1
Connector Type	MPO Female
Polish Type	APC
Cable Jacket Ratings	PVC(OFNR)/LSZH
Connectors Color	Green
Cable Jackets Color	Yellow
Trunk Length	0.2m
Cable Diameter	3.0mm
Polarity	Type B

ITEM	Description
Insertion Loss	SM:APC \leq 0.35dB
Return Loss	SM:APC \geq 60dB
Wavelength	1310/1550nm
Operating Temperature	-25~75°C
Storage Temperature	-40~85°C

Polarity: Type B

P1		P2	P3
Pin No.	Connection	Pin No.	Pin No.
1	----->	12	-
2	----->	11	-
3	----->	-	12
4	----->	-	11
5	Not used	-	-
6	Not used	-	-
7	Not used	-	-
8	Not used	-	-
9	<-----	-	2
10	<-----	-	1
11	<-----	2	-
12	<-----	1	-

Technical Drawing



Cable Length	Tolerances
$L \leq 1m$	+150mm/-0
$1m < L \leq 30m$	+150mm/-50
$L > 30m$	+1%/-0

Ordering Information

$\frac{\text{MPO/F/APC}}{1} - \frac{\text{MPO/F/APC}}{2} - \frac{\text{G657.A1}}{3} - \frac{8B}{4} - \frac{\text{B3.0}}{5} - \frac{3M/2.8M}{6} - \frac{\text{LSZH}}{7} - \frac{\text{Yellow}}{8} - \frac{B}{9}$

- 1-Connector A: MPO/F/APC:MPO Female APC;
- 2-Connector B: MPO/F/APC:MPO Female APC;
- 3-Fiber Type: G657.A1;
- 4-Fiber Count: 8B:8F Bundled Cable;
- 5-Breakout Type: B3.0: 3.0mm Breakout Cable;
- 6-Cable Length: 3M/2.8M: Cable total length 3M, branch length 2.8M;
- 7-Cable Jacket Ratings: LSZH; PVC(OFNR);
- 8-Cable Color: Yellow(G657.A1);
- 9-Polarity: B: Type B;



SHKE Communication Tech Co.,Ltd.

Add: 3/F, Building 1, Future Science Park,
No.1026 Songbai Road, Xili, Nanshan District
Shenzhen 518055 China

E-mail: market@shke.com.cn

Web: www.shke.com.cn